

TECHNICAL DETAILS

MA10 Integral front sight.

Height: 8,5 mm (.335).
Dovetail: 3/8" X 30° X 2 mm (.0787) height.

MA11/ 12 / 13 Rocky Mountain front sight.

Dovetail: 3/8" X 30° X 2,5 mm (.0984) height.
MA-11: height 8,5 mm (.335).
MA-12: height 9,5 mm (.374).
MA-13: height 11 mm (.433).

MA14 German silver front sight:

Height: 9,8 mm (.385).
Dovetail: 3/8" X 30° X 2 mm (.0787) height.

MA15 Integral hooded front sight with adj. elev.

Dovetail: 3/8" X 30° X 2 mm (.0787) height.

MA16 Integral gold bead front sight, for HAWKEN.

Height: 12 mm (.472).
Dovetail: 9 mm (.360) X 30° X 2 mm (.0787) height.

TA21 Adjustable rear sight for HAWKEN.

Suitable to 15/16" (cal. 45 and 50) and 1" (cal. 54) barrels.
Fixing with 9 mm (.360) dovetail insert.

TA22 Notched rear blade.

Height: 9,5 mm (.374).
Dovetail: 3,8" X 30° X 2,5 mm (.0984) height.

TS031/32/33/34 Folding rear sight, for SLUG

Dovetail: 20 mm (.790) X 30° X 3 mm (.122) height.

TC82 - TC83 M & H

Folding rear sight with windage and elevation adj.
Windage adj. for TC82 only: 3 mm (.122).
Dovetail: 3/8" X 30° X 2,5 mm (.0984) height.
TC82-83/M height adj. 11 ÷ 13,4 mm (.433 ÷ .527).
TC82-83/H height adj. 13,4 ÷ 15,8 mm (.527 ÷ .622).

BAR01 - BAR03 M & H

Base with folding rear sight adj. in windage and elevation For barrels Ø
19 ÷ 21 mm (.748 ÷ .826).
Windage adjustment 3 mm (.122).
Fixing: with two 3 MA or 6x48 screws (specify).
Center to center distance: 14,3 mm (9/16").

BAR01/M: height adj. 11,5÷13,5 mm (.445÷.525).
BAR01/H: height adj. 13,5÷15,7 mm (.525÷.620).

BAR03/M: height adj. 10,8÷12,8 mm (.422÷.500).
BAR03/H: height adj. 12,8÷15 mm (.500÷.620).

BAR05 SERIES

Rear sight with dovetail windage and elevation adj.

BAR05/R:
Standard for barrel: Ø 19÷21 mm (.748÷.825).
Fixing with two 3 MA or 6x48 screws (specify).
Center to center distance: 14,3 mm (9/16").
Adjustment in height:
With FG5: 9,7 ÷ 12,4 mm (.384÷.490).
With FG6: 10,8 ÷ 13,5 mm (.428÷.535).
With FG7: 12 ÷ 14,6 mm (.470÷.575).
With FG9: 14,2 ÷ 16,8 mm (.555÷.660).
With FD1: 10 ÷ 12,6 mm (.393÷.496).

BAR08 Rear sight with windage and elevation adj.

Standard for barrels Ø 19÷21 mm (.748÷.826).
Height adj. 10,5 ÷ 13,5 mm (.413 ÷ .530).
Fixing: with one 3 MA or 6x48 screw (specify).
Center to center distance: 14,3 mm

BAR09 Rear sight with windage and elevation adj.

For barrels Ø 19 ÷ 21 mm (.748 ÷ .826).
Fixing: with two 3 MA or 6x48 screws (specify).
Center to center distance: 14,3 mm (.9/16").
Height adjustment: 10÷14 mm (.395÷.550).

MC52/B/G/F & L Rifle front sight.

Heights: 5 mm (.196), 5,5 mm (.216), 6 mm (.236), 6,5 mm (.255), 7 mm (.275), 7,5 mm (.295),
8 mm (.315), 8,5 mm (.334), 9 mm (.354),
9,5 mm (.374), 10 mm (.393).
Dovetail: 5,20 mm (.204)X15° X 2 mm (.0787) height.

MC55/B/G & L STREAMLINED RIFLE FRONT SIGHT.

Heights: 7 mm (.275), 8 mm (.315),
9 mm (.354), 10 mm (.393),
11 mm (.433), 12 mm (.473.),
Width = Height.
Dovetail: 3/8" X 30° X 2,5 mm (.0984) height.

MC56 /B/G/F & L Ramp style front sight.

Heights: 7 mm (.275), 8 mm (.315),
9 mm (.354), 10 mm (.393),
11 mm (.433), 12 mm (.473.),
Width = 9 mm (.354).
Dovetail: 3/8" X 30° X 2,5 mm (.0984) height.

MC80/G/F & L Integral ramp front sight.

Heights: 14,5 mm (.570), 15,5 mm (.610),
16,5 mm (.650), 17,5 mm (.690),
18,5 mm (.728), 19,5 mm (.767),
20,5 mm (.807).
Fixing with 3 MA or 6x48 screws (specify).
Center to center distance: 25,4 mm (1").
For barrel: Ø 14 ÷ 16 mm (.550 ÷ .630).

MC90F / MC90B Ramps with adj. front sight.

Height adjustment: from 14 mm (.216) to 18 mm (.708)
For barrels: Ø 14 ÷ 16 mm (.550 ÷ 630).
Fixing with 3 MA or 6x48 screws (specify).
Center to center distance: 35.8 mm (1.41).

RC68/V & S Ramps for MC56 front sights.

Height: 5,2 mm (.204).
Width: 9 mm (.354).
For barrels: Ø 14 ÷ 16 mm (.550 ÷ 630).
RC68/V: Fixing with two 3 MA or 6x48 screws (specify).
Center to center distance: 16 mm (.630).

RC70/V & S Ramps for MC52 front sights.

Height: 5,5 mm (.216).
Width: 9 mm (.354).
For barrels: Ø 14 ÷ 16 mm (.550 ÷ 630).
RC70/V: Fixing with two 3 MA or 6x48 screws (specify).
Center to center distance: 16 mm (.630).

RC90/V Ramp for MC56 front sights.

Height: 7 mm (.275).
Width: 9 mm (.354).
For barrels: Ø 14 ÷ 16 mm (.550 ÷ 630).
Fixing with two 3 MA or 6x48 screws (specify).
Center to center distance: 50,8 mm (2").